



## Magnetic Strainer

Protect your valuable pumping equipment from metal particulates and unwanted debris

### Features


- Magnetized stem for removal of light ferrous material
- Compact design
- Easy to access for cleaning
- Variety of straining holes available
- Fully drainable in vertical or horizontal position
- Can be cleaned-in-place, once trapped particulates are removed

### Applications


- Bulk unloading stations (truck receiving)
- Equipment protection
- Small particulate straining
- Metallic debris removal from products with large particulates

# TrueClean® Magnetic Strainer

Circular Strain Shape



Elongated Strain Shape



## Item Number Configuration

**TMS - 15 M 2 P - E - 316L - 7**

**Size**

- 15 = 1.5"
- 20 = 2.0"
- 25 = 2.5"
- 30 = 3.0"

**Strain Size**

- 1 = 1/8"
- 2 = 1/4"
- 3 = 3/8"
- 4 = 1/2"
- 5 = 5/8"

**Strain Shape**

- P = Circular (standard)
- S = Elongated slots

**Material & Finish**

- 316L
- stainless steel\*
- 32 Ra ID / OD
- \*AL-6XN® alloy also available

**Connection**

- M = Standard pressure
- Tri-Clamp® (standard)
- W = Butt weld

**Elastomer**

- E = EPDM (standard)
- Y = Viton
- G = Teflon

## Dimensions

Size	A	B	C	D
1.5	18	9 7/8	4 3/8	5 3/8
2	14 1/8	7 7/8	4 1/8	5 3/8
2.5	17 1/8	10 5/8	5 1/8	5 3/8
3	15 3/8	8 5/8	4 7/8	5 3/8

\*All dimensions are shown in inches.

